


Diesel Generator sets



Model	GF-20	GF-30	GF-46	GF-75	GF-80	GF-100	GF-108	GF-150	GF-160	GF-200
Rated Power (kW)	20	30	46	75	80	100	108	150	160	200
Model	4B3.9-G	4B73.9-G	4BTA3.9G	6BT5.9G1	6BT5.9G2	6BTA5.9G2	6BTA4.9G2	6CTA8.3G2	6CTA4.3G2	6LTA4.9G2
Rated output(kw)	24	36	50	86	92	110	120	163	183	220
Max output(kw)	27	40	55	93	100	120	130	180	200	240
Governing method	Mechanical/Electronic				Electronic					
Intaking method	Natural aspirated	Turbocharged			Turbocharged					
Oil volume(L)	9.5			14.3			16	23.8	26	27.5
Displacement(L)	3.92			5.88			8.3		8.9	
Cylinder numbers	4			6						
Fuel Consumption (g/kw.h)	≤225			≤210						≤199
Cooling Starting Method	Closed water cooled/electric starting									
Model	WT-184F	WT-184H	WT-224E	WT-274C	WT-274C	WT-274D	WT-274E	WT-274H	WT-274H	WT-274K
Rated output (kW)	20	30	48	80	80	96	112	160	160	200
Rated Capacity (KVA)	25	37.5	60	100	100	120	140	200	200	250
Rated Voltage (V)	400,415,440/200,208,220V 416,440,480/208,220,240									
Frequency (Hz)	50/60									
Power Factor (COSΦ)	0.8					0.8 lagging				
Phase / Connection	3-phase 4-wire					Y type connection				
Excitation	brushless									
Voltage Regulation	A.V.R.									
Net Weight(kg)	650	700	830	1360	1460	1530	1700	1970	2050	2300
Packing size LWH(cm)	1800X900X1250		1800X900X1300	2350X920X1350		2380X920X1350		2450X980X1500		2600X980X1500

Specifications given herein are subject to change without notice



MATIMBAHOUSE (PTY) LTD

16 Thora Crescent, Wynberg, 2090
 PO Box 95146, Grant Park, 2051
 Johannesburg, South Africa
 Tel: +27 (0) 11 444 2061
 Fax: +27 (0) 11 444 8416